Tech Specs

Quick Specs TypeNetwork computer Form FactorDesktop slimline Processor1 x AMD Sempron 1.5 GHz Processor Main FeaturesHyperTransport RAM1 GB (installed) / 2 GB (max) Flash Memory2 GB (installed) / 4 GB (max) Hard DriveNo HDD Graphics Controller ATI Mobility Radeon X700 Audio OutputIntegrated **Networking**GigE PowerAC 120/230 V (50/60 Hz) OS Provided Microsoft Windows XP Embedded Dimensions (WxDxH)3.2 in x 8.9 in x 12.1 in Manufacturer Warranty3 years warranty General TypeNetwork computer Product Form FactorDesktop slimline Built-in DevicesSpeaker **Processor / Chipset** CPUAMD Sempron 1.5 GHz CPU Qty1 Max CPU Qty1 Processor Main FeaturesHyperTransport Chipset TypeAMD M690E

RAM
Installed Size1 GB / 2 GB (max)
Flash Memory
Flash Memory2 GB (installed) / 4 GB (max)
Hard Drive
TypeNo HDD
Monitor
Monitor TypeNone.
Graphics Controller
TypeIntegrated
Graphics ProcessorATI Mobility Radeon X700
Video InterfacesDVI
Max Monitors Supported2
Audio Output
TypeIntegrated
Input Device
TypeMouse, keyboard
Keyboard
InterfacePS/2
Mouse
TechnologyOptical
Networking
TypeIntegrated
Data Link Protocol Ethernet, Fast Ethernet, Gigabit Ethernet
Expansion / Connectivity
Slots1 (total) / 1 (free) x PCIe - half-length, full-height (x4 mode)
Interfaces
• 1 x DVI-I

- 2 x serial
- 1 x DVI-D
- 6 x USB 2.0 (2 in front)
- 1 x LAN (Gigabit Ethernet)
- 1 x microphone

- 1 x audio line-out
- 1 x PS/2 mouse
- 1 x PS/2 keyboard
- 1 x parallel

Miscellaneous

Included Accessories Vertical stand

FeaturesSecurity lock slot (cable lock sold separately)

Mounting InterfaceYes

Power

Device TypePower adapter

Nominal VoltageAC 120/230 V (50/60 Hz)

Power Provided65 Watt

Power Consumption Operational 14.1 Watt

Operating System / Software

OS ProvidedMicrosoft Windows XP Embedded

SoftwareWyse Device Manager Workgroup Edition

Manufacturer Warranty

Service & Support3 years warranty

Service & Support DetailsLimited warranty - 3 years

Dimensions & Weight

Width3.2 in

Depth8.9 in

Height12.1 in

Environmental Parameters

Min Operating Temperature50 °F

Max Operating Temperature104 °F

Humidity Range Operating20 - 80%